

Model	Replacement	Rated Capacity	Operating Pressure Range	Operating Temp. Range	Rated Flow
EQ-600	EQ-600R	600,000 gallons 2,271,247.07 liters	20-100psi 137.89-689.47kPa	40-90° F 4.44-32.2° C	7.0 gpm 26.49 lpm
Manufactured by: Aquasana, Inc. 6310 Midway Road · Haltom City, Texas 76117 · 866.662.6885					

This system has been independently tested according to NSF/ANSI Standard 42 for the reduction of the substances listed below.

NSF/ANSI 42	Influent Challenge Chlorine	Minimum Reduction	Overall % Reduction	Results
Chlorine Reduction, Free Available	2 mg/L ±10%	≥50%	>96.9%	Pass

Data Summary Table

Sample Point	Accumulated Volume (gal)	Dynamic Pressure (psi)	Chlorine, Free Available (mg/L)		Flow Rate (gpm)
			Influent	Effluent 1	
Startup	150	61	2.2 ND (0.05)	ND (0.05)	7.1
10%	60,000	61	2.2 ND (0.05)	ND (0.05)	7.0
20%	120,000	60	1.9 ND (0.05)	ND (0.05)	7.0
30%	180,000	60	2.2 ND (0.05)	ND (0.05)	7.0
40%	240,000	60	2.1 ND (0.05)	ND (0.05)	7.0
50%	300,000	60	2.1 0.05	0.05	7.0
60%	360,000	61	2.1 ND (0.05)	NtD (0.05)	7.1
70%	420,000	60	2.2 0.09	0.09	7.1
80%	480,000	61	1.9 ND (0.05)	ND (0.05)	7.1
90%	540,000	61	2.0 ND (0.05)	ND (0.05)	6.9
100%	600,000	61	2.0 0.18	0.18	7.1



Testing was performed under standard laboratory conditions, actual performance may vary.

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.