🕒 aquasana.

PERFORMANCE DATA SHEET

Model	Replacement	Rated Capacity	Operating Pressure Range	Operating Temp. Range	Rated Flow					
AQ-MF-1	AQ-MF-1-R	784 gallons 2,967 liters	10-125 psi 68.95-861.8 kPa	35-100° F 1.66-37.78° C	1.5 gpm 5.67 lpm					
Manufactured by: Aquasana Inc. 6310 Midway Road - Haltom City, Texas 76117 - 866 662 6885										

This system has been tested according to NSF/ANSI Standards 42, 53, & 401 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42, 53 & 401.

NSF/AN	ISI 42		Minimum Reduction	Overall % Reduction	Results	Table 8.2 - Perfor for organic chem	mance data she	et reducti	ion clain
Chlorine Available		on, Free	<0.5 mg/l	96.06%	Pass	VOCs (by surrogate testing	Drinking water regulatory level	Influent/ Unfiltered	Effluent/ Filtered
Chloramine Reduction, Free		<0.5 mg/l	96.06%	Pass	using chloroform)	(MCL/MAC) mg/L	mg/L	mg/L	
Available Particulate Class I					alachlor	0.002	0.050	0.001	
(particles 0.5			85%	99.9%	Pass	atrazine	0.003	0.100	0.003
						benzene	0.005	0.081	0.001
NSF/ANSI 53 Minim			Minimum	Overall %	Results	carbofuran	0.04	0.190	0.001
			Reduction	Reduction		carbon tetrachloride	0.005	0.078	0.0018
Asbestos		on	99%	>99%	Pass	chlorobenzene	0.1	0.077	0.001
Cyst Red		11.6.5	99.95%	>99.95%	Pass	chloropicrin	_	0.015	0.0002
Lead Rec			<10 ug/L	>99.4%	Pass	2,4-D	0.07	0.110	0.0017
Lead Rec			<10 ug/L	>99.3%	Pass	dibromochloropropane (DBCP)	0.0002	0.052	0.00002
		on pH 6.5	2 ug/L	>96.6%	Pass	o-dichlorobenzene	0.6	0.080	0.001
		on pH 8.5	<2 ug/L	96.7%	Pass	p-dichlorobenzene	0.075	0.040	0.001
MTBE Re		: 1 (250.4) 2	<5 ug/L	86.6%	Pass	1,2-dichloroethane	0.005	0.088	0.0048
Perfluoro	octanoio	acid (PFOA) & sulfonate (PFOS)	0.07 ug/L	95.2%	Pass	1,1-dichloroethylene	0.007	0.083	0.001
Turbidity			<0.5 NTU	99.1%	Pass	cis-1,2-dichloroethylene	0.07	0.170	0.0005
,			See Table			trans-1,2-dichloroethylene	0.1	0.086	0.000
VOC Surr	rogate Te	est (as chloroform)	8.2	99.4%	Pass	1,2-dichloropropane	0.005	0.080	0.001
						cis-1,3-dichloropropylene	_	0.030	0.001
NSF/AN	ISI 401	Reduction Requirement	Minimum Reduction	Overall % Reduction	Results	dinoseb	0.007	0.170	0.0002
Atenolol		30 ng/L	94.2%	94.2%	Pass	endrin	0.002	0.053	0.00059
Bispheno		300 ng/L	98.80%	98.9%	Pass	ethylbenzene	0.7	0.035	0.001
Carbama		200 ng/L	98.6%	98.6%	Pass	ethylene dibromide (EDB)	0.00005	0.000	0.00002
DEET	izepine	200 ng/L	98.7%	98.7%	Pass	haloacetonitriles (HAN)	0.00005	0.044	0.00002
Estrone		200 ng/L	96.30%	96.5%	Pass	bromochloroacetontrile		0.022	0.0005
buprofer	n	60 ng/L	95.3%	95.4%	Pass		_	0.022	0.0005
Linuron		20 ng/L	96.6%	96.6%	Pass	dibromoacetontrile	—	0.024	0.0008
Meproba	mate	60 ng/L	94.7%	94.7%	Pass	dichloroacetontrile	_		0.0002
Metolach		200 ng/L	98.6%	98.6%	Pass	trichloroacetontrile	-	0.015	0.0003
Vaproxer		20 ng/L	96.3%	96.4%	Pass	haloketones (HK)		0.0070	0.0001
Nonyl ph		200 ng/L	97.50%	97.5%	Pass	1,1-dichloro-2-propanone	-	0.0072	0.0001
Phenytoi		30 ng/L	95.50%	95.6%	Pass	1,1,1-trichloro-2-propanone	-	0.0082	0.0003
TCEP		700 ng/L	98%	98%	Pass	heptachlor (H-34, Heptox)	0.0004	0.025	0.00001
ГСРР		700 ng/L	97.8%	97.8%	Pass	heptachlor epoxide	0.0002	0.0107	0.0002
rimetho	prim	20 ng/L	96.7%	96.7%	Pass	hexachlorobutadiene	-	0.044	0.001
Vicroplastic			97.3%	99.4%	Pass	hexachlorocyclopentadiene	0.05	0.060	0.000002
o.5 to <1 µn	m)	particles/mL				lindane	0.0002	0.055	0.00001
						methoxychlor	0.04	0.050	0.0001
VATER QUALIT		System certified				pentachlorophenol	0.001	0.096	0.001
O RESEARCH AND THE			dards 42, 53 & 401 and as			simazine	0.004	0.120	0.004
			ostantiated by test data. Performance Data Sheet for			styrene	0.1	0.150	0.0005
(specific contam			CELIUI	1,1,2,2-tetrachloroethane	-	0.081	0.001
∕®						tetrachloroethylene	0.005	0.081	0.001
All conta	iminants	reduced by this fi	lter are listed	d.		toluene	1	0.078	0.001
Not all contaminants listed may be present in your water.				2,4,5-TP (silvex)	0.05	0.270	0.0016		
Does not remove all contaminants that may be present in your water.				tribromoacetic acid	-	0.042	0.001		
The contaminants covered in NSF/ANSI 401 have been deemed as			1,2,4-trichlorobenzene	0.07	0.160	0.0005			
incidental/emerging compounds and have been detected in drinking			1,1,1-trichloroethane	0.2	0.084	0.0046			
water supplies at trace levels. These compounds can affect some			1,1,2-trichloroethane	0.005	0.150	0.0005			
consumers' perception of drinking water quality.		trichloroethylene	0.005	0.180	0.0010				
Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.				trihalomethanes (THMs)		Influent/ Unfiltered	Effluent/ Filtered		
Click here to view the system's warranty						bromodichloromethane (THM)			
<u>Click here to view the system's warranty.</u>			bromoform (THM)	0.080	0.300	0.015			
Filter is only to be used		Systems certified for cyst			chloroform (THM)	0.060	0.300	0.015	
	rith cold wa		red v	uction may be	e used on	chlorodibromomethane (THM)			
			· disi	nfected water	's that may cysts.	xylenes (total)	10	0.070	0.001

Testing was performed under standard laboratory conditions, actual performance may vary.

disinfected waters that may contain filterable cysts.